

KABLE KONTROL® Cyclone® Heavy Duty Spiral Wrap Tubing



- MSHA Certified
- UV Resistant
- Manufactured From HDPE for Ultimate Protection Against Abrasion & Crushing Damage
- Resists All Hydraulic Fluids Including Glycol & Phosphate ester
- Rounded Edges For Reduced Risk of Exposed Sharp Edges
- Operating Temperature Range (-40°F to 280°F)
- Developed to Increase The Service Life of Hydraulic Hoses
- Wide Range of sizes Fits Most Hose Diameters

Heavy Duty HDPE hydraulic hose spiral wrap Tubing helps protect your investment from damage and wear. HDPE hydraulic hose wrap is ideal for heavy-duty bundling and hydraulic hose protection. As the name suggests Cyclone® Heavy Duty Spiral Wrap is an HDPE (High-Density Polyethylene) protective spiral hose wrap designed specifically for heavy-duty bundling and protection of hydraulic and pneumatic hoses used across various industries. It serves as a cost-effective and quick method for minimizing heavy production losses. Cyclone® hydraulic hose spiral wrap protects against production losses and damage caused by depreciation, abrasion, regular misuse, poor maintenance, or severe working environments. HDPE Heavy Duty Spiral Wrap is available in a wide range of dimensions and fits



Temp Range	MATERIAL	Approvals
-40C to 138C	HDPE (high density poly-ethylene)	MSHA 140862

PART NUMBER	Nominal OD (mm/inch)	Nominal ID (mm/inch)	Wall Thickness (mm/inch)	Pitch (mm/inch)	FEET/BOX
HGPW-12-165	12mm/0.47"	9mm/0.35"	1.5mm/0.059"	10mm/0.39"	165'
HGPW-16-165	16mm/0.63"	12.6mm/0.50"	1.7mm/0.067"	12mm/0.47"	165'
HGPW-20-66*	20mm/0.79"	16mm/0.63"	2mm/0.079"	16mm/0.63"	66'
HGPW-20-165	20mm/0.79"	16mm/0.63"	2mm/0.079"	16mm/0.63"	165'
HGPW-25-66*	25mm/0.98"	20.6mm/0.81"	2.2mm/0.087"	20mm/0.79"	66'
HGPW-25-165	25mm/0.98"	20.6mm/0.81"	2.2mm/0.087"	20mm/0.79"	165'
HGPW-32-66*	32mm/1.26"	27mm/1.06"	2.5mm/0.098"	22mm/0.87"	66'
HGPW-32-165	32mm/1.26"	27mm/1.06"	2.5mm/0.098"	22mm/0.87"	165'
HGPW-40-66*	40mm/1.57"	34.6mm/1.36"	2.7mm/0.106"	27mm/1.06"	66'
HGPW-40-165	40mm/1.57"	34.6mm/1.36"	2.7mm/0.106"	27mm/1.06"	165'
HGPW-50-66*	50mm/1.97"	44mm/1.73"	3.0mm/0.118"	30mm/1.18"	66'
HGPW-63-66*	63mm/2.48"	55.4mm/2.18"	3.8mm/0.150"	37mm/1.46"	66'
HGPW-75-66*	75mm/2.95"	67mm/2.64"	4.0mm/0.157"	42mm/1.65"	66'
HGPW-90-66*	90mm/3.54"	80mm/3.15"	5.0mm/0.197"	45mm/1.77"	66'
HGPW-110-40*	110mm/4.33"	99mm/3.90"	5.5mm/0.220"	50mm/1.97"	40'
HGPW-125-40*	125mm/4.92"	113mm/4.45"	6.0mm/0.240"	55mm/2.17"	40'

* Available in Black or Yellow HDPE

Note: All outer and inner dimensions are nominal

Wall Thickness Tolerance +/- 0.2mm

Pitch Tolerance +/-1.00mm

