

Scotch[®]

Lacquer Masking Tape

2060



Technical Data

May, 2003

Product Description Scotch[®] Lacquer Masking Tape 2060 masks lacquer paints from surfaces from other types of paints and lacquers.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Crepe paper	Rubber	Green	60 yds. (54.8 m)

Typical Physical Properties **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	34 oz./in. width (37 N/100 mm width)	D-3330
Tensile Strength:	24 lbs./in. width (420 N/100 mm width)	D-3759
Elongation at Break:	8%	D-3759
Tape Thickness:	.0060 in. (0.15 mm)	D-3652
Temperature Use Range:	Up to 200°F (93°C) for one hour	

Features

- Rubber adhesive for instant adhesion which sticks easily and helps reduce labor.
- Remains supple which helps resist slivering off the job and resists curl off when coated with paints and lacquers.
- Crepe paper backing for easy handling and tear which helps reduce time involved.
- Solvent and moisture resistant to help resist curl off.
- Controlled unwind.
- Remove at a 90° angle as it removes with little or no adhesive transfer to most surfaces for up to three days after application, even when subjected to sunlight exposure.
- Designed for indoor use only as it should not be subjected to outdoor exposure or prolonged periods of sunlight as tape may become very difficult to remove.

Scotch[®] Lacquer Masking Tape

2060

Storage	Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.
----------------	---

Shelf Life	To obtain best performance, use Scotch [®] Lacquer Masking Tape 2060 within one year from date of manufacture.
-------------------	---

For Additional Information	To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/industrialtape . Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.
-----------------------------------	---

Important Notice	3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.
-------------------------	--

Limitation of Remedies and Liability	If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.
---	---

ISO 9002

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.