## SELF-DUMPING STEEL HOPPER W/BUMPER RELEASE - D-50-MD \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 47 7/16" -43 5/16" -33 9/16" -DUMPED **POSITION** LOAD CENTER ( 76° 42 3/16" 38 1/16" **DUMPED** ANGLE CENTER OF **GRAVITY** 21 13/16" 13 9/16" **@** 10" 22 1/4" -CONTACT 7 1/2" X 2 1/2" 26' 23 5/8" **RELEASE** USABLE FORK **LEVER** 51 7/8" **POCKETS** 66 3/8" DIMENSION TOLERANCE ± 1/4" STANDARD FEATURES I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION MODEL NUMBER: D-50-MD NEVER EXCEED LOAD CENTER RATING PER FORK REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE VOLUME: 1/2 CU. YDS. TRUCK MANUFACTURER'S GUIDELINES. Ρ CAPACITY: 4,000 LBS. DO NOT USE THIS FORK TRUCK ATTACHMENT IF Ρ OVERALL WIDTH: 33 9/16" LOAD WILL EXCEED FORK TRUCK AND LOCAL REGULATIONS AND STANDARDS. R **OVERALL LENGTH: 51 7/8"** ANY MODIFIED UNITS ARE NON-RETURNABLE MANUFACTURER'S LOAD CENTER RATING. 0 OVERALL HEIGHT: 38 1/16" [ ] As marked [ ] As drawn V APPROX. WEIGHT/ LOST LOAD=435.07 LBS. PULL CABLE IS AT LEAST: 48" Α Signed: Date: MINIMUM EFFECTIVE THICKNESS= LESS THAN 1" **TOUGH BAKED IN POWDER COATED BLUE FINISH Printed Name:** LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING SPECIAL FEATURES DISTRIBUTOR'S NAME: FOR INTERNAL USE ONLY NONE PROJECT SIGN OFF **VESTIL MANUFACTURING** W.O.# **SALES** DATE: 5/7<u>/08</u> SALES: X W. STALEY ENG. reference: X SCALE: 1:16 FILE NAME: \*\*\*ADDITION OF CASTERS MAY CHANGE WEIGHT FAB. CAPACITY BASED ON CASTER RATING\*\*\* QUOTED LEAD TIME: $_{ m Y}$ QUOTE # 37-007-050

POWER

Χ