APPROX WEIGHT: 170.35 lbs.

Χ

DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!! \*\*\* ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE \*\*\* ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 78" **USABLE LENGTH** 6 1/8"±1/8" 7 3/8" 93 1/8" FORK EXTENSION MATERIAL **OVERALL LENGTH** THICKNESS IS 5/16" 39 5/16' Ø 5/8" 1/2"-(25/16") 5 1/2" CENTER OF GRAVITY -USABLE STANDARD FEATURES **WIDTH** SPECIAL FEATURES **MODEL NUMBER IS FE-5-90-RS OVERALL WIDTH IS 6 1/8"** NONE DIMENSION TOLERANCE ± 1/4" **OVERALL WIDTH W/LOOP IS 7 3/8"** I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS **USABLE WIDTH IS 5 1/2'** REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO Α **OVERALL LENGTH** IS 93 1/8" CONFIRM PRODUCT AND INSTALLATION Ρ **USABLE LENGTH IS 78"** COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Ρ **OVERALL HEIGHT IS 4 1/16"** AND LOCAL REGULATIONS AND STANDARDS. R FITS 5" WIDE x 2" MAX. THICKNESS FORK ANY MODIFIED UNITS ARE NON-RETURNABLE 0 SOLID STEEL CONSTRUCTION [ ] As drawn [ ] As marked V TOUGH BAKED IN POWDER COATED YELLOW FINISH Α APPROX. WEIGHT / LOST LOAD = 170.35 LBS. PER PAIR Date: Signed: MINIMUM EFFECTIVE THICKNESS = LESS THAN 1" CAPACITY = 4,000 # PER PAIR, EVENLY DISTRIBUTED Printed Name: FORK EXTENSIONS DO NOT CHANGE THE LOAD LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING CENTER OF EXISTING FORK TRUCK. DISTRIBUTOR'S NAME: FOR INTERNAL USE ONLY NEVER EXCEED LOAD CENTER RATING PER FORK PROJECT SIGN OFF TRUCK MANUFACTURER'S GUIDELINES VESTIL MANUFACTURING W.O.# DO NOT USE THESE FORK EXTENSIONS IF LOAD WILL **SALES** DATE: 7/8/16 SALES: X EXCEED FORK TRUCK MANUFACTURER'S LOAD **C.CLEMENS** ENG. CENTER RATING. SCALE: 1:14 FILE NAME: REFERENCE: FORK EXTENSIONS MUST NOT EXCEED 150% FAB. ORIGINAL FORK LENGTH. QUOTED LEAD TIME: X QUOTE # 08-007-377 POWER