

**TraFFix
Devices Inc.**



**Water-Wall™
Water-Filled Barrier**

Engineered Products for Safer Highways



#45032-O
Orange Water-Wall

#45032-W
White Water-Wall

- MASH Eligible, TL-2 Longitudinal Channelizing Device
- NCHRP-350 Tested and Passed, TL-1 Barrier Wall, TL-2 Longitudinal Channelizing Device and TL-3 Barricade
- 32" tall x 72" long. Low profile allows motorists in all vehicle types to view oncoming traffic at intersections.
- Durable linear low density polyethylene plastic minimizes cracking and breaking.
- Double wall knuckle design minimizes breakage and creates a strong connection at hinge points.
- Hinge design allows for a 30-degree pivot between sections.
- Large 8" fill hole speeds filling process, includes twist-lock plastic cap.
- Tamper resistant, offset drain plug with coarse buttress thread - screws in or out in only 2.5 turns.
- Includes one steel connection pin and keeper pin per wall to allow sections to be locked together.
- Forklift and pallet jack slots are molded in for easy movement.
- Standard colors are orange/red or white - additional colors available upon request.
- Accepts the Water-Wall chain link fence for additional job site security.



Water-Wall™

Water-Filled Barrier



30-degree pivoting hinge design allows the TraFFix Water-Wall to handle curved roads

Water-Wall®



Specification


Water-Wall to be 72" long x 32" tall x 18" wide and molded from linear low density polyethylene. Water-Wall to be MASH Eligible as a Longitudinal Channelizing Device, TL-2. Individual wall shall weigh 80 lbs. empty and 1,110 lbs. filled. Standard colors are white or orange. Water-Wall sections are connected together with galvanized steel T-pins passing through a double wall knuckle which minimizes breakage at hinge points. Wall shall pivot up to 30 degrees when connected. Water-Wall to have one 8" diameter fill hole for quick fill and a twist lock cap for closure. Water-Wall will have molded through holes to provide easy movement. Drain plug to be offset to protect against cracking or breaking and have coarse buttress threads for quick removal and attachment. Water-Walls shall stack for easy movement and storage.



Water-Wall stacks for storage and transportation



Water-Wall Fence can be easily attached to Water-Wall for additional job-site security.



TROUS POUR CHARIOT ÉLÉVATEUR TROU DE VIDANGE AVEC FILETAGE RENFORCÉ



Water-Wall can be easily lifted and placed using a forklift or pallet jack



Large 8" fill hole speeds filling process, includes twist-lock plastic cap



Water-Wall can pivot 30-degrees and be locked together with steel connection pins



New tamper resistant, offset drain plug with coarse buttress thread

MASH Eligible As:

TL-2 Longitudinal Channelizing Device - WZ-358

NCHRP 350 Approved As:

TL-1 Longitudinal Barrier - HSA-10/B-130

TL-2 Longitudinal Channelizing Device - HSA-10/WZ-224

TL-3 Barricade - HSA-10/WZ-224

Specifications:

Length:	72 in.		1.82 m
Height:	32 in.		0.81 m
Width:	18 in.		0.46 m
Weight (empty):	80 lbs.		36.30 kg.
Weight (filled w/water):	1,110 lbs.		503.50 kg.
Material:	Linear Low Density Polyethylene		
Color:	Orange/Red or White		

Distributed by:

**TraFFix
Devices Inc.**



Engineered Products for Safer Highways

160 Avenida La Pata, San Clemente, CA 92673

(949) 361-5663 FAX (949) 361-9205

www.traffixdevices.com